

## Portable Circular Saw K 55 cc in the T-MAX

ref.no.: 918002

EAN: 4032689196053

► Transport and storage box T-MAX



### Technical data

Cutting depth	0 – 58 mm
Cutting depth at 45°	0 – 48 mm
Tilt range	0 – 45 °
Nominal No. of strokes – no load	5700 1/min
Nominal power input	1300 W
Weight	4,1 kg
Universal motor	230 V / 50 Hz

### Delivery specification

1 TCT saw blade 168 x 1.2/1.8 x 20 mm, AT, 24 teeth, for cross-cutting wood; Ref. No. 092478

1 Allen key 5 mm; Ref. No. 093034

1 Mains cable 4 m (13.1 ft); Ref. No. 087323

## Examples for usage



The innovative pointer automatically follows the machine as it is tilted and therefore always accurately tracks the actual cutting edge.



The chips are carried away so efficiently that the vacuum channel cannot become blocked. Users enjoy this crucial benefit when executing plunge cuts in the direction of the fibers as well.



Dispensing with a detachable riving knife, the FLIPPKEIL permits reliable, convenient and straightforward plunge cutting.



Using the MAFELL guide rails or optional edge guide, which is graduated in millimeters, decking boards can be made to fit exactly.

## Applications

---

- ▶ Cross-cutting and rip cuts
- ▶ Bevel cuts up to 45°
- ▶ Plunge cuts
- ▶ Compatible materials include solid wood, boards, planks and various board materials

## Advantages

---

- ▶ Healthy working environment – due to a clean workplace and a clear view of the saw blade thanks to optimal dust extraction with the MAFELL Dust Extractors.
- ▶ The pivoting guard is retracted quickly and easily by means of a lever for convenience and safety when executing bevel and plunge cuts.
- ▶ Bright LEDs illuminate a large working area.

## Description

---

With the compact and ultra-performing K 55 cc, you can achieve superb quality cuts at depths of up to 58 millimeters – and this from a portable circular saw with the best power-to-weight ratio in its class.

It is no longer necessary to unscrew the riving knife – the FLIPPKEIL offers you optimum user-friendliness and safety when plunge cutting.

Sheer power and high torque take on a whole new meaning with the new high-output CUprex motor. It offers performance-optimized digital electronics and newly developed control technology. Its speed is continuously variable according to the nature of the material and application.

## Accessories / Tools



**Guide rail F 80**  
0,8 m (2,6 ft) long



**Guide rail F 160**  
1.6 m (5.2 ft) long



**Guide rail F 310**  
3,1 m (10,2 ft) long



**Angle fence F-WA**



**Flexible hose FXS-L**  
up to 3,2 m (10.6 ft) long



**Guide pocket set**  
2 x F 160 + F-VS + 2 x F-SZ 100 MM + 1 guide pocket



**End cap F-EK**  
2 pieces



**Parallel guide fence K55-PA**



**Dust bag**



**TCT saw blade**  
168 x 1,2/1,8 x 20 mm, Z 24, WZ, for universal use with wood



**TCT saw blade**  
168 x 1,2/1,8 x 20 mm, Z 32, WZ, for fine sawing in wood



**Non-slip profile F-HP 6,8 M**  
6.8 m (22.3 ft.) long



**Guide rail F 110**  
1.1 m (3.6 ft) long



**Guide rail F 210**  
2,1 m (6,9 ft) long



**Connecting piece F-VS**  
for joining two guide rails



**Suction clamping system Aeroxfix F-AF 1**  
with 1,3 m rail, adapters for above and underneath rail, flexible hose



**Guide pocket F 160**  
for guide rails up to 1,6 m



**Guide pocket set**  
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 100MM + Guide pocket



**Screw clamp F-SZ 100MM**  
2 pieces, for fixing guide rail to workpiece



**Roller edge guide MF-UA**



**TCT saw blade**  
168 x 1,2/1,8 x 20 mm, Z 16, WZ, for ripping in wood



**TCT saw blade**  
168 x 1,2/1,8 x 20 mm, Z 56, WZ, for cross-cutting wood



**Splinter guard F-SS 3,4M**  
3.4 m (11.2 ft.) long

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)