

KSP 40 Flexistem in the T-MAX

ref.no.: 915801

EAN: 4032689143095

► Compact package in space-saving T-MAX



Technical data

Cutting depth off rail	0 - 42 mm
Cutting depth 45° with track	0 - 29 mm
Cutting depth on rail	0 - 40 mm
Tilt range	0 - 45 °
Flexi-Guide effective length	1400 mm
Nominal No. of strokes – no load	8400 1/min
Nominal power input	900 W
Weight	2,2 kg
Universal motor	230 V / 50 Hz

Delivery specification

- 1 Flexi-Guide FX 140, 1.4 m (4.6 ft) with splinter guard; Ref. No. 204372
- 1 TCT saw blade 120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth; Ref. No. 092558
- 1 Parallel guide fence; Ref. No. 203180
- 2 Clamping claws; Ref. No. 203773
- 1 Hose connector; Ref. No. 203782
- 1 Mains cable 4 m (13.1 ft); Ref. No. 087323

Examples for usage



A handy machine combined with a guide rail ensure high precision, as shown when cutting doors to length.



World first: the special steel guide rail can be rolled up to save space.



Everything you need for the KSP 40 Flexistem is immediately to hand in the practical T-MAX carrying case.



No problem: shadow gaps with a gap width of 13 mm and above.

Applications

- ▶ Rip cuts and cross-cutting
- ▶ Bevel cuts up to 45°
- ▶ Plunge cuts
- ▶ Shadow gaps from 13 mm
- ▶ Compatible materials include board materials, doors, worktops, lathing, cladding and internal finishing and renovation materials

Advantages

- ▶ Four saws in one: portable circular saw, rail-mounted portable saw with pivoting guard, plunge-cut saw and shadow gap saw.
- ▶ Pivot point alongside rail. Only one marking pointer irrespective of angle and with or without rail.
- ▶ First saw in its class with a lever to retract the pivoting guard.

Description

The KSP 40 Flexistem is a unique portable sawing system comprising a 40-series circular saw and a compact guide rail in a practical carrying case. The benefits to joiners, carpenters and interior decorators are self-evident:

This box of tricks contains everything you need when working on site, for cutting panels to size, sawing shadow gaps, and shortening doors. The relevant sawing system is quickly assembled whatever the job. In conjunction with the innovative Flexi-Guide, the compact and rugged KSP 40 Portable Circular Saw provides an ideal solution for practically every type of cut. Supplied together with a practical carrying case, it's an unbeatable combination.

Accessories / Tools



Screw clamp
for fixing guide rail to workpiece



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ FT/TT 40
teeth, for fine sawing



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth,
for universal use in wood



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 12 teeth,
for ripping



Flexi-Guide rail FX 140
1,4 m (4.6 ft) with splinter guard

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de