

Cordless Cross-Cutting System KSS 40 18M bl PURE in T-MAX

ref.no.: 919802

EAN: 4032689193465

▶ Transport and storage box T-MAX



Technical data

Cutting depth at 0° with guide track	0 – 40 mm
Cutting depth 45° with track	0 – 27 mm
Cutting depth at 0° without guide track	0 – 42 mm
Tilt range	0 – 45 °
Cutting length	300 mm
Angle cuts	+45 – -60 °
Nominal No. of strokes – no load	6700 1/min
Weight with guide rail	3,65 kg
Battery	18 V, 94 Wh, Li-Ion

Delivery specification

- 1 TCT saw blade 120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth; Ref. No. 092558
- 1 Parallel guide fence; Ref. No. 203180
- 1 Hose connector; Ref. No. 203782
- 1 Dust bag; Ref. No. 206787
- 1 Allen key 4 mm; Ref. No. 093074

Examples for usage



One system, five saws, one case: the KSS 40 can be used as a cross-cut saw, plunge-cut saw, shadow gap saw or portable circular saw with or without the Flexi-Guide FX 140 for extra guidance when cutting.



Fastening the portable circular saw to the KSS rail creates a very practical single-handed cross-cutting system.



Perfect edging: the circular saw's spacers enable you easily to make exact expansion joint cuts with widths from 13 mm (1/2 in.).



In combination with the roll-up Flexi-Guide FX 140, precise guided cuts up to 1.4 m (4.6 ft) long can be executed with consummate ease.

Applications

- ▶ Cross cuts with guide
- ▶ Rip cuts and cross-cutting
- ▶ Plunge cuts, recesses and cutting shadow gaps from 13 mm (1/2 in.)
- ▶ Compatible materials include board materials, doors, worktops, parquet and laminate flooring, solid wood

Advantages

- ▶ The new, compact brushless motor is extremely durable, efficient and maintenance-free.
- ▶ The quick-release catch enables you to detach the machine from the rail in a single, quick action. The saw can then be used as a separate portable circular unit with all the functionality of the MAFELL K series.
- ▶ With a cutting depth of 40 mm on the rail, virtually all sawing tasks arising during on-site assembly work can be executed – and in keeping with immaculate MAFELL quality standards to boot.
- ▶ One stop is fixed while the other can be adjusted exactly thanks to the large scale markings – for precise angle cuts.

Description

We have not reinvented cross-cutting – but we have made it easier and more portable. And with the new KSS 40 18M bl, we have even added a battery: one that delivers what it promises - innovative battery technology for maximum performance.

When it comes to internal finishing work, there is no better helper than the KSS 40 18M bl, whatever the task in hand: be it for floors, walls, doors, furniture, ceilings or roof battens – to make cross or rip cuts, rail-guided cuts, miter or compound miter cuts at angles up to 45°, or even plunge cuts.

Backed by 25 years of experience, it takes cross-cutting system technology to the next development level with the addition of state-of-the-art battery technology.

Accessories / Tools



Screw clamp
for fixing guide rail to workpiece



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ FT/TT 40
teeth, for fine sawing



Battery PowerTanks 18 M 94
18 V, 94 Wh



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth,
for universal use in wood



Flexi-Guide rail FX 140
1,4 m (4.6 ft) with splinter guard



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 12 teeth,
for ripping



TCT saw blade
120 x 1,2/1,8 x 20 mm / 40 trapezoidal teeth , for
laminare



Battery-PowerStation APS 18 M
18 V



Dust bag
cpl.

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de