

Pull-Push Saw ERIKA 60 E



ref.no.: 971501

EAN: 4032689128160

▶ boxed



Technical data

Cutting height	2 - 61 mm
Cutting height at 45°	2 - 42 mm
Tilt range	-2 - 47 °
Cutting length	217 mm
Table top dimensions	412 x 544 mm
Nominal power input	1300 W
Weight	21 kg
Universal motor	230 V / 50 Hz
Working height with stand	310 mm
Working height without stand	845 mm

Delivery specification

- 1 TCT saw blade 190 x 1.2/2.0 x 30 mm (7 1/2 in.), AT, 36 teeth, for universal use in wood; Ref. No. 092550
- 1 Universal guide fence with fence extension; Ref. No. 200941
- 1 Allen key 5 mm; Ref. No. 093034
- 1 Extraction hose with 2 connectors; Ref. No. 093639
- 1 Push stick; Ref. No. 034901
- 1 Mains cable 4 m (13.1 ft); Ref. No. 097765

Examples for usage



Applications

- ▶ Cross and rip cuts
- ▶ Circular saw bench functionality
- ▶ Bevel cuts up to 47°
- ▶ Compatible materials include solid wood, board materials, parquet and laminate flooring, aluminum profiles and plastics

Advantages

- ▶ New type of suction channel revolutionises extraction - for less dust when working.
- ▶ Maximum cutting height of 61 mm (2 3/8 in.) – with a material thickness of 12 mm (1/2 in.), a cutting length of 215 mm (8 7/16 in.) is achieved.
- ▶ For hidden cuts – the riving knife can be lowered with no effort.
- ▶ With voltage loss switch for protection against uncontrolled reconnection after a power interruption.

Description

With optimum air flow in the suction channel, chips can be more easily removed by your dust extractor.

At 21 kg (46.3 lbs), the ultra-lightweight is convenient for use on any floor. Whether in the cellar or in the attic – the ERIKA 60 E can be carried quickly and effortlessly from one workplace to another.

Operation of the ERIKA 60 E is simple in its design concept. Clearly designed operating elements are all arranged logically on the front of the machine. Over 30 years of experience have gone into every detail. Stability where it's needed – on the table! Especially when cutting, the craftsman exerts pressure on the workpiece and thus also on the benchtop.

Stability where it's needed - on the table! Especially when cutting, the craftsman exerts pressure on the workpiece and thus also on the benchtop.

Attention ERIKA-users: All accessories of the previous models ERIKA 55 and ERIKA 60 can continue to be used on the new ERIKA 60 E.

Accessories / Tools



Fold-away support



Extension table
for mounting LO 50 E (2 supporting rails
required)



Supporting rail
650 mm (25 9/16 in.) long

Supplementary support plate



Dust bag



TCT saw blade
180 x 1.2/1.8 x 30 mm (7 1/16 in.), AT, 30 teeth,
for universal use



Fence guide extension
with telescopic rod and drop stop



Sliding table



Router adapter kit



Supporting rail
840 mm (33 1/16 in.) long



Universal guide fence
with fence extension



TCT saw blade
190 x 1.2/2.0 x 30 mm (7 1/2 in.), AT, 36 teeth,
for universal use



TCT saw blade
180 x 1,2/2,0 x 30 mm (7 1/16 in.), AT, 56, teeth

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de