

## Multi-cutter MF 26 cc GF-MAX in the T-MAX

ref.no.: 917802

EAN: 4032689184135

- ▶ With wallboard cutter MF-GF 90
- ▶ Transport and storage box T-MAX



### Technical data

Cutting depth	0 - 26 mm
Nominal No. of strokes – no load	3600 - 6250 1/min
Nominal power input	1400 W
Universal motor	230 V / 50 Hz
Weight	4,9 kg

### Delivery specification

- 1 TCT saw blade 120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth; Ref. No. 092558
- 1 Wallboard cutter MF-GF 90/15, for 90° V-grooves up to 15 mm deep; Ref. No. 206590
- 1 Parallel guide fence; Ref. No. 206038
- 2 Position indicators; Ref. No. 206012
- 1 Mains cable 4 m (13.1 ft); Ref. No. 087323

## Examples for usage

---



The MF-AF 90 can be used for routing and folding techniques, as applied in facade construction and with sign boards.



Three slots can be cut in one pass with the MF-SE 3. This quick and simple bending technique is applied to produce curved elements.



The MF-GF 90 cuts 90° V-grooves with very little dust; by gluing the cut faces, sturdy corner paneling is produced in just a few steps.



Equipped with the MF-VN 25, the multicutter can produce grooves for risers or service ducts efficiently and quickly.

## Applications

---

- ▶ Lengthwise and crosswise grooves
- ▶ V-grooves
- ▶ For routing wallboard prior to folding, bending techniques
- ▶ Routing and folding techniques with aluminum composite panels, sawing.
- ▶ Materials usage: solid wood, MDF, drywall, aluminum composite panels

## Advantages

---

- ▶ Turn the adjusting screw to set the cutting depth on the sliding scale with an accuracy of 1/10 mm.
- ▶ Enhanced precision assured – The glider slides on the surface of the workpiece and thus prevents tilting. It helps to hold the MF 26 cc securely in position when it is mounted on the guide rail as well. When bending and folding aluminum composite panels and wallboard in particular, the glider ensures exact cutting depth accuracy.
- ▶ The guard opens with a single action. When it is opened, the starting lockout and sawblade lock engage automatically.
- ▶ With or without a rail – simply turn the pointer to show the exact cutting depth.

## Description

---

The design of the MF 26 cc is characterized by the use of extremely rugged, high-quality and precision-made parts, including the lightweight magnesium die-cast housing and impact-resistant, fiber glass-reinforced plastic components.

The MF 26 cc multi-cutter can be operated to a cutting depth of 26 mm (1 in.) on the guide rail and as a plunge-cut saw.

Whether sawing, routing or cutting grooves, genuine precision is best achieved with the aid of the guide rail system F.

Continuously variable speed up to 6250 rpm. For shaping, sawing and slotting an abundance of different materials.

## Accessories / Tools



**Guide rail F 80**  
0,8 m (2,6 ft) long



**Guide rail F 160**  
1.6 m (5.2 ft) long



**Guide rail F 310**  
3,1 m (10,2 ft) long



**Connecting piece F-VS**  
for joining two guide rails



**Guide pocket F 160**  
for guide rails up to 1,6 m



**Guide pocket set**  
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 100MM  
+ Guide pocket



**Suction hose LW 35** – 4 m long,  
anti-static (13.1 ft)  
for use when machining solid wood



**Screw clamp F-SZ 100MM**  
2 pieces, for fixing guide rail to workpiece



**Wallboard cutter MF-GF 45**  
for 45° V-grooves up to 15 mm deep (incl. 2  
position indicator)



**Reversible TCT knife**



**Aluminum composite cutter MF-AF 135**  
for 135° V-grooves up to 8 mm deep (incl. 2  
position indicators and 1 chip deflector)



**TCT saw blade**  
120 x 1.2/1.8 x 20 mm / 40 trapezoidal teeth , for  
laminat



**TCT saw blade**  
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ FT/TT 40  
teeth, for fine sawing



**Chamfer knives**  
22 x 22 x 2 mm



**Guide rail F 110**  
1.1 m (3.6 ft) long



**Guide rail F 210**  
2,1 m (6,9 ft) long



**Guide track 770**  
max. tilt range 770 mm (30 5/16 in.)



**Angle fence F-WA**



**Guide pocket set**  
2 x F 160 + F-VS + 2 x F-SZ 100 MM + 1 guide  
pocket



**End cap F-EK**  
2 pieces



**Guide fence, cpl.**



**Roller edge guide MF-UA**



**Wallboard cutter MF-GF 90/15**



**Aluminum composite cutter MF-AF 90**  
for 90° V-grooves up to 8 mm deep (incl. 2  
position indicators and 1 chip deflector)



**Slotting head MF-SE 3**  
for cutting 3 slots up to 26 mm on guide rail F



**TCT saw blade**  
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 12 teeth,  
for ripping



**Expanding groove cutter MF-VN 25**  
Cutting width 15.4 - 25 mm



**Reversible TCT knife**



Splinter guard F-SS 3,4M  
3.4 m (11.2 ft.) long



Non-slip profile F-HP 6,8 M  
6.8 m (22.3 ft.) long



TCT saw blade  
120 x 1.2/1.8 x 20 mm (4 3/4 in.) AT, 24 teeth,  
for universal use in wood

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)