

## Dust Extractor S 25 L

ref.no.: 919715

EAN: 4032689189741

► boxed



### Technical data

Bin capacity	25 l
Bin water capacity	20 l
Hose connector	Ø 66 / 58 mm
Low air pressure	248 mbar
Dimensions (W x L x H)	425 x 380 x 570 mm
Volume flow rate	220 m³/h
Nominal power input	1200 W
Weight	13,2 kg
Universal motor	230 V / 50 Hz

### Delivery specification

1 Folded filter cassette, 1 pair, polyester (8600cm²); Ref. No. 093674

1 Extraction hose 4 m (13.1 ft), Ø 27 mm (1 1/16 in.), anti-static with bayonet lock Ø 6 mm (2 5/8 in.), hose connector Ø 35 mm (1 3/8 in.); Ref. No. 093684

1 Non-woven filter bag, 21 l useful capacity

1 Mains cable 8 m; Ref. No. 078207

## Examples for usage

---



Clean and easy: the hose connector with 35 mm soft cone allows not only MAFELL power tools to be connected simply, but other makes too.



Made of a special plastic, the 25l tank is extremely resilient and durable. It also resists corrosion and all customary acids and alkalis.



The new type of filter system, which is especially efficient, has been designed specifically for use with power tools.



The hose is antistatic. The user is thus protected against electrostatic discharges (electric shock), and dust residue is less likely to cling to the hose.

## Applications

---

- ▶ For wet and dry pick-up
- ▶ For picking up waste
- ▶ Compatible materials include dust, chips, liquids

## Advantages

---

- ▶ Conveniently located on the front of the appliance are the on/off switch, the switch for automatic vibration and pulse filter cleaning/vibration, the speed control for adjusting the suction force, and the volume flow indicator.
- ▶ Practical hose connection - with quick-release/bayonet lock plus additional catch.
- ▶ Automatic shutdown with wet suction - by means of sensors when maximum capacity is reached.
- ▶ When used for wet suction cleaning, the appliance cuts out automatically when its maximum capacity is reached.

## Description

---

Whether sawing, drilling or sanding, the innovative MAFELL dust extractors are designed to keep the workplace clean.

The S 25 L model is tested for compliance with dust class L and, in view of its substantial dust retention capacity (99 %), is suitable for use as a standard industrial and commercial vacuum cleaner.

All the appliances are equipped with microprocessor-controlled electronics for safe and efficient operation. The features include smooth starting, which eases the load on both the appliance and the power circuit, and automatic running-on to ensure that the hose is emptied when the extractor is switched off. In addition, the speed control allows the suction force to be adjusted according to the extent of contamination and the hose diameter.

A long service life is ensured by the high-performance motor fan with bypass cooling. Ideal for wet and dry suction cleaning.

Thanks to the automatic on/off switch, the MAFELL dust extractors can be used for extracting the dust created by all other makes of power tool as well. All the MAFELL models are also suitable for picking up liquids.

## Accessories / Tools

---



**Folded filter cassette**  
1 pair, polyester (8600 cm<sup>2</sup>)



**Extraction hose 5 m (16 ft.)**  
Ø 35 mm (1 3/8 in.) with soft cone 35 mm (1 3/8 in.), torsion joint, Ø 66 mm (2 5/8 in.) bayonet, anti-static



**Extraction hose 4 m (13.1 ft.)**  
Ø 27 mm (1 1/16 in.) with soft cone 35 mm (1 3/8 in.), torsion joint, Ø 66 mm (2 5/8 in.) bayonet, anti-static



**Hand-held extraction set D 35**  
2 tubes, 1 floor nozzle, 1 handle, 1 hose D 35, 2.5 m



**Reducing socket**  
58 / 35 mm



**Extraction hose 4 m (13.1 ft.)**  
Ø 21 mm (13/16 in.) with soft cone 35 mm (1 3/8 in.), torsion joint, Ø 66 mm (2 5/8 in.) bayonet, anti-static



**Extraction hose 2,5 m (8.2 ft)**  
49 mm (1 15/16 in.) with cone 58 mm (2 5/16 in.), torsion joint, 66 mm (2 5/8 in.) bayonet, static



**Non-woven filter bags V-FB 35 – pack of 5**  
5 pieces, packed



**T-MAX**  
Carrying case size IV

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)