

Dust Extractor S 25 M



ref.no.: 919710

EAN: 4032689189765

MAX-holder

boxed





Technical data

Hose connector	Ø 66 / 58 mm
Low air pressure	248 mbar
Volume flow rate	220 m³/h
Nominal power input	1200 W
Universal motor	230 V / 50 Hz
Bin capacity	25 I
Bin water capacity	20
Dimensions (W x L x H)	500 x 405 x 565 mm
Weight	13,2 kg

Delivery specification

- 1 Extraction hose 4 m (13.1 ft), Ø 27 mm (1 1/16 in.), anti-static with bayonet lock Ø 6 mm (2 5/8 in.), hose connector Ø 35 mm (1 3/8 in.); Ref. No. 093684
- 1 Folded filter cassette, 1 pair, polyester (8600cm²); Ref. No. 093674
- 1 MAX-holder
- 1 Non-woven filter bag, 21 I useful capacity
- 1 Mains cable 8 m; Ref. No. 176030

mafell@mafell.de 1 / 5



Examples for usage



The T-MAX case con-taining a power tool can easily be mounted on the S 25 M or S 50 M for transportation.



Once secured to the appliance, the T-MAX can serve as a bench for small workpieces.



Clean and easy: the hose connector with 35 mm soft cone allows not only MAFELL power tools to be connected simply, but other makes too.



The new type of filter system, which is especially efficient, has been designed specifically for use with power tools.

mafell@mafell.de 2 / 5



Applications

- For wet and dry pick-up
- For picking up waste
- Compatible materials include dust, chips, liquids

Advantages

- The control panel on the front gives easy access to the dials for selecting the desired suction mode and hose diameter.
- ▶ When used for wet suction cleaning, the appliance cuts out automatically when its maximum capacity is reached.
- ► The M-class dust extractors are supplied with a handy mounting plate for accommodating a MAFELL-MAX/T-MAX case
- Practical hose connection with quick-release/bayonet lock plus additional catch.

Description

Whether sawing, drilling or sanding, the innovative MAFELL dust extractors are designed to keep the workplace clean.

All the appliances are equipped with microprocessor-controlled electronics for safe and efficient operation. The features include smooth starting, which eases the load on both the appliance and the power circuit, and automatic running-on to ensure that the hose is emptied when the extractor is switched off. In addition, the speed control allows the suction force to be adjusted according to the extent of contamination and the hose diameter.

The S 25 M and S 50 M models are tested for compliance with dust class M and, in view of their substantial dust retention capacity (99,9%), suitable for use as standard industrial and commercial vacuum cleaners.

A long service life is ensured by the high-performance motor fan with bypass cooling. Ideal for wet and dry suction cleaning.

Thanks to the automatic on/off switch, the MAFELL dust extractors can be used for extracting the dust created by all other makes of power tool as well. All the MAFELL models are also suitable for picking up liquids.

mafell@mafell.de 3 / 5



Accessories / Tools



Folded filter cassette

1 pair, polyester (8600 cm²)

- Extraction hose 5 m (16 ft.)
 Ø 35 mm (1 3/8 in.) with soft cone 35 mm (1 3/8 in.), torsion joint, Ø 66 mm (2 5/8 in.) bayonet, anti-static
- Extraction hose 4 m (13.1 ft.)
 Ø 27 mm (1 1/16 in.) with soft cone 35 mm (1 3/8 in.), torsion joint, Ø 66 mm (2 5/8 in.)
 bayonet, anti-static



Hand-held extraction set D 35

2 tubes, 1 floor nozzle, 1 handle, 1 hose D 35, 2.5 \mbox{m}



Reducing socket

58 / 35 mm

- Extraction hose 4 m (13.1 ft.)
 Ø 21 mm (13/16 in.) with soft cone 35 mm (1 3/8 in.), torsion joint, Ø 66 mm (2 5/8 in.) bayonet, anti-static
- Extraction hose 2,5 m (8.2 ft)
 49 mm (1 15/16 in.) with cone 58 mm (2 5/16 in.), torsion joint, 66 mm (2 5/8 in.) bayonet, static
- Non-woven filter bags V-FB 35 pack of 5
 5 pieces, packed



T-MAX

Carrying case size IV

mafell@mafell.de 4 / 5



contact

MAFELL AG

Beffendorfer Straße 4 D-78727 Oberndorf / Neckar Germany Tel.: +49 7423 / 812-114 Fax: +49 7423 812-102 Email: export@mafell.de

mafell@mafell.de 5 / 5