

Chain Mortiser LS 103/40 Ec complete with chain set $28 \times 40 \times 100$ mm (1 1/8 x 1 9/16 x 3 15/16 in.)



ref.no.: 924201

EAN: 4032689059105

boxed



Technical data

Mortising depth	100 / 150 mm
Nominal No. of strokes – no load	4050 1/min
Nominal power input	2500 W
Weight	8,7 kg
Universal motor	230 V / 50 Hz

Delivery specification

1 Stop plate; Ref. No. 200954

1 Allen key 4 mm; Ref. No. 093074

1 Allen key 8 mm; Ref. No. 093070

1 Mains cable 10 m (32.8 ft); Ref. No. 087612




Examples for usage



Tenon cuts of various sizes up to 100 mm (3 15/16 in.) with the LS 103 Ec.



The LS 103 Ec with the guide support stand FG 150 for mortising depths of up to 140 mm.



Dimensions of mortising chains example: 28 x 40 x 100 mm; chain width: 28 mm (1 1/8 in.); hole width: 40 mm (1 9/16 in.); mortising depth: 100 mm (3 15/16 in.)



The LS 103 Ec being operated horizontally.



Applications

- For cutting mortises
- Compatible materials include solid wood and glue-laminated timber

Advantages

- Figonomic handle and switch arrangement for safe, efficient, energy-saving work.
- Low machine weight ideal for use on construction site.
- Extremely powerful motor for high efficiency and considerable time-saving.

Description

Unique lightweight at only 8.7 kg (19.2 lbs.). Chain mortising without the drag.

The long guide plate has a large adjusting range and permits work on large timber workpieces.

The tensioning system of the LS 103 Ec allows fast chain replacement. Even retightening of the chain without removing the chain guard is quick and easy.

Optional accessories include the guide support stand for the LS 103 Ec, ideal for precise framing work, particularly indispensable for chain sets of 150 mm (5 7/8 in.)

With the LS 103 Ec and the appropriate slot mortising attachment SG 230, SG 400 or SG 500, you can execute slots of up to 500 mm (19 11/16 in.). This is not possible with any other machine on the market!



Accessories / Tools

	Chain bars 28 x 40 x 100 mm (1 1/8 x 1 9/16 x 3 15/16 in.)		Guide support stand FG 150 for mortising depth to 140 mm
-	Chain bars 28 x 40 x 150 mm(1 1/8 x 1 9/16 x 5 7/8 in.)		Chain bars 28 x 35 x 100 mm (1 1/8 x 1 3/8 x 3 5/16 in.)
-5	Chain bars 28 x 35 x 150 mm (1 1/8 x 1 3/8 x 5 7/8 in.)		Mortising chain pitch 22.6, 28 x 35 x 100 mm (1 1/8 x 1 3/8 x 3 5/16 in.)
	Mortising chain pitch 22.6, 28 x 40 x 150 mm (1 1/8 x 1 9/16 x 5 7/8 in.)	ank:	Sprocket pitch 22.6, 4 teeth, for set 28 x 35/40 x 100 mm/150 mm (1 1/8 x 1 9/16 x 3 15/16 / 5 7/8 in.)
8888	Replacement chain links + rivets 1 bag, for 28 mm (1 1/8 in.) chain width, large pitch		



contact

MAFELL AG

Beffendorfer Straße 4 D-78727 Oberndorf / Neckar Germany Tel.: +49 7423 / 812-114 Fax: +49 7423 812-102 Email: export@mafell.de